



BITUBOND ALUMINIUM SOLAR REFLECTIVE PAINT

Bituminous Aluminium Reflective Coating



Description

A thin, bituminous based aluminium protective coating of brushing consistency that dries to a silvery finish.

Uses

Bond It ALUMINIUM SOLAR REFLECTIVE PAINT is a light/heat reflective coating that will provide protection against solar degradation and heat gain. It is suitable for use over bituminous coatings, aged asphalt and primed steel. It is not suitable for direct application to expanded polystyrene.

Preparation

All surfaces must be structurally sound, clean, dry and free from surface contaminants such as grease, rust and dirt. If necessary, remove any organic growth i.e. lichen, with a fungicidal wash such as Bond It Mould Stop. If the surface is still dusty after cleaning, or covered with weathered bitumen, prime with BITUMEN PRIMER and allow to dry.

Application

STIR VERY THOROUGHLY BEFORE USE. Do not thin. Apply immediately and continue stirring periodically during use. Apply by brush or mohair roller. When brushing, use soft bristle brushes applying the lightest of pressure.

Over recently applied bituminous surfaces allow the following minimum periods to elapse after the final coat has dried before applying ALUMINIUM SOLAR REFLECTIVE PAINT:-

hot applied coatings	-	24 hours
solvent based coatings	-	10 days
water based coatings	-	14 days

Apply 2 coats, the second coat being applied as soon as the first coat is dry.

Over bituminous surfaces apply the thinnest coat necessary to obliterate the black colour of the bitumen coating for the first coat. The second coat should also be thin. Avoid the formation of pools.

Do not apply when rain, frost or overnight dew are expected before the coating is fully dry, as bronzing of the surface may result if these conditions are not

observed.

When applying to large areas on bright days it is advisable to wear polarized sunglasses to reduce glare.

Drying Time

Approximately 1 hour depending on temperature, humidity, air and base conditions.

Safe Handling Precautions

Please refer to separate material safety data sheet for full handling, use and storage instructions. Keep out of reach of children. It is the user's responsibility to determine suitability for use. If in doubt contact our Technical Department for advice.

Note: this information is for general guidance only, since site conditions and labour are beyond our control. It is recommended that users make their own tests to determine suitability.

Disposal of Containers

Do not leave containers on site where residue could be a hazard to children, animals or the environment. Replace lids securely and remove any containers to a central disposal point.

Cleaning Of Tools

Clean with paraffin (kerosene) or white spirit.

Storage Conditions

Store under cover away from sources of heat and ignition. Keep containers sealed when not in use. Storage temperature should be between 5°C and 40°C.

Storage Life

Shelf life of this product is a minimum of 5 years under good storage conditions in original unopened containers.

Specification Summary

Type of solvent	Petroleum Hydrocarbons
Approximate Flashpoint Test Method BS2000:Part 170:1982 [IP170/75 (81)]	40°C
Approximate Specific Gravity	1.0
Approximate Coverage	4 - 6m ² per litre (dependant on substrate porosity)
Service Temperature Limits	-30°C to +90°C depending on operating conditions
Application Temperature Limits	Normally 5°C to 30°C
Chemical Resistance	Resistant to: water and most salt solutions Not Resistant to: acids, alkalis and solvents
Fire Resistance	WET: Flammable DRY: Will burn slowly
UN Number	1263

Container Sizes

Size:	2.5 Litre	5 Litre	25 Litre
Code:	BDB030	BDB021	BDB022
Barcode:	5060021367914	5060021362117	5060021362384

The data presented in this leaflet are in accordance with the present state of our knowledge, but do not absolve the user from carefully checking all supplies immediately on receipt. We reserve the right to alter product constants within the scope of technical progress or new developments. The recommendations made in this leaflet should be checked by preliminary trials because of conditions during processing over which we have no control, especially where other companies raw materials are also being used. The recommendations do not absolve the user from the obligation of investigating the possibility of infringement of third parties rights and, if necessary clarifying the position. Recommendations for use do not constitute a warranty, either express or implied, of the fitness or suitability of the products for a particular purpose.



Certificate Number: 6152
ISO 9001
ISO 14001



BOND IT
Unit G16 River Bank Way, Lowfields Business Park, Elland,
West Yorkshire HX5 9DN.
Telephone: +44 (0)1422 315300 Fax +44 (0)1422 315310
Email: sales@bond-it.co.uk Website: www.bond-it.co.uk



V2 01/3/17
Supersedes V2 22/3/12